

Internal transporting conveyors:



The internal transporting conveyor is used for hanging garments, trolley or different products less than 40kg.

We also produce wide range of conveyors for transport and sorting the garments with hanger or trolley.

Our conveyors have the main role to:

- Transform the traditional static into dynamic warehouse with automation systems and inserting eventual sorting system.
- Automatic conveyor for single products counting.
- Automatic straightening of garments.

PIN transporter (Hanger transport)



Made of aluminum profile, the pin transporter, on one side has a chain roll installed and moved by gearbox, on the other side a special steel profile to support the plastic contour, in order to process a better flow of the hangers.

The translation of the garments is achieved through the so called dragging chain with cylinders and 80mm spacing, that provide safe and silent operating even with high load.

The structure of a pin transporter is simple, particularly silent, has low consumption and simple maintenance.

The maximum speed is round 35 meter per minute.

Clip transporter (hanger transport)



This transporter is made out of special bended aluminum. It's circumference including height and weight are proportionally adapted in order to save space.

The mechanical translation is composed from continuous chain, made from rolls, positioned on guide rail. This completely protected system, together with some other control systems, assure reliable and silent goods transport, even with high load.

Maximum speed can go from 5 till 35 meters per minute.

The automatic transfer station allow secure connection of other system forms.

Transport for ironing area



Manual push transport - Exchange (hanger transport)

